

Brass NMO Style Series with Gold Contact Pin and Brass Nut Ring Mount

3/4" hole; 1-1/8"-18 thread; installs from above. Accomodates thickness up to 0.046 inches.

Model	Length of Coax	Coax	Connector	Type
NMO58AU-NC	17'	RG-58A/U	None	N/A
NMO34	17'	N/A	None	N/A
NMOPFP195-NC	17'	Pro-Flex™ Plus 195	None	N/A
NMO58U-NC	17'	RG-58/U	None	N/A
NMO58UBN	17'	RG-58/U	BNC	Crimp
NMO58UFFME	17'	RG-58/U	Female FME*	Crimp
NMOPFP195FFME	17'	Pro-Flex™ Plus 195	Female FME*	Crimp
NMOPFP195MSMA	17'	Pro-Flex™ Plus 195	Male SMA	Crimp
NMOPFP195RPC	17'	Pro-Flex™ Plus 195	Reverse Polarity TNC	Crimp
NMO58AUSP	17'	RG-58A/U	PL259	Solder
NMO58AUCP	17'	RG-58A/U	PL259	Crimp
NMO58UCP	17'	RG-58/U	PL259	Crimp
NMO58UCP	17'	RG-58/U	PL259	Crimp
NMOPFP195C	17'	Pro-Flex™ Plus 195	TNC	Crimp
NMO58UC	17'	RG-58/U	TNC	Crimp
NMO58UPL	17'	RG-58/U	Mini-UHF	Crimp
NMO58AUPL	17'	RG-58A/U	Mini-UHF	Crimp



NMO

* Connectors are attached on these models only. For all other models, connectors are shipped loose. Connectors may be attached upon request for an additional charge.