

Quick Cabinet Selection Guide

Image	Model	Material	Classification	Dimensiones (mm)			Mounting		Special Characteristics
				Width	Length	Depth	Post	Wall	
	TXG-2919-S	PBT/PC BLEND	NEMA 4X, IP67	290	190	100	TX-PROM5, TXPRO-M4V2	Included	Requiere Panel: TX-5070
	TXG-3040	PBT/PC BLEND	NEMA 4X, IP67	300	400	160	TX-PROM5, TXPRO-M1V2	TXGKIT3	Includes Panel
	TXG-4050	PBT/PC BLEND	NEMA 4X, IP67	400	500	160	TX-PROM5, TXPRO-M3V2	TXGKIT3	Includes Panel
	TXG-5070	PBT/PC BLEND	NEMA 4X, IP67	500	700	250	TXPRO-M2	Included	Requiere Panel: TXG1929-P/L
	TXT2535	PC Transperent, PBT/PC BLEND	NEMA 4X, IP67	250	350	150	TXPRO-M1V2	TXGKIT3	Includes Panel
	TXT3545	PC Transperent, PBT/PC BLEND	NEMA 4X, IP67	350	450	200	TXPRO-M1V2	TXGKIT3	Includes Panel
	TXT4050	PC Transperent, PBT/PC BLEND	NEMA 4X, IP67	400	500	160	TX-PROM5, TXPRO-M3V2	TXGKIT3	Includes Panel
	TX-MTB-6P	Polyester: PBT + PC	IP67	55	85	40	N/A	Included	Cuenta con terminales
	TX-MTB-6P	Polycarbonate+ ABS	IP67	90	75	40	N/A	Included	Únicamente para interior. Cuenta con terminales
	TX-PCG-1520	Polyester: PBT + PC	IP67	150	200	100	N/A	N/A	
	TX-PCG-1010S	Polyester: PBT + PC	IP67	100	100	75	N/A	N/A	
	AR-18161-0CHSC	Polyester Fiberglass	NEMA 4X	406,4	457,2	254	N/A	Included	Includes accessories for fan mounting Recommended 2 fans model 1708473 w(not included)
	A1-086-CHSCFG	Polyester Fiberglass	NEMA 4X	203	254	152	TXPROM5	Included	Cover with security screws

Image	Model	Material	Classification	Dimensions (mm)			Mounting		Special Characteristics
				Width	Length	Depth	Post	Wall	
	ENC-196YG	Fiberglass polyester	NEMA 4X	229	155	79	N/A	N/A	Lower cover for wiring
	TXG-0138	Plastic ABS	IP65	170	251	101	N/A	TXGKIT3	Prepared for DIN rail installation with toggle lock
	TXG-0146	Plastic ABS	IP65	185	285	180	TX-PROM5	TXGKIT3	Prepared for DIN rail installation with toggle lock
	TXG-0147	Plastic ABS	IP65	285	285	155	TX-PROM5	TXGKIT3	Prepared for DIN rail installation with toggle lock
	TXG-0149	Plastic ABS	IP65	350	460	165	TX-PROM5	TXGKIT3	Prepared for DIN rail installation with toggle lock
	TXG-014	Plastic ABS	IP65	100	68	50	N/A	TXGKIT3	Close with screws
	TXG-012	Plastic ABS	IP65	158	90	60	N/A	TXGKIT3	Close with screws
	TXG-02-28	Plastic ABS	IP65	248	77	87	N/A	TXGKIT3	Close with screws
	TXG-01-52	Plastic ABS	IP65	120	120	60	N/A	Incluido	Close with screws
	TXG-01-11	Plastic ABS	IP65	180	125	57	N/A	TXGKIT3	Close with screws Cable management
	TXG-01-57	Plastic ABS	IP65	300	300	90	TX-PROM5	Incluido	Close with screws
	TXG-01571	Plastic ABS	IP65	300	300	150	TX-PROM5	Incluido	Close with screws

Image	Model	Material	Classification	Dimensions (mm)			Mounting		Special Characteristics
				Width	Length	Depth	Post	Wall	
	TXG-018	Plastic ABS	IP65	115	88	55	N/A	Included	Close with Screws
	TXG-015	Plastic ABS	IP65	160	160	90	N/A	TXGKIT3	Close with Screws Transparent lid
	TXG-015-TS	Plastic ABS	IP65	160	160	90	N/A	TXGKIT3	Close with Screws Transparent lid
	TXG-02-35JK	Aluminum	IP65	560	380	265	TX-PROM5	TXGKIT3	Toggle Lock
	TXG-03-53	Aluminum	IP65	252	215	91	TX-PROM5	Included	Close with Screws
	TXG-03-83	Aluminum	IP65	390	280	158	TX-PROM5	TXGKIT3	Close with Screws
	PST-4040-20A	Steel	IP66	250	300	150	TX-PROM5	N/A	Resistance against impact IK10. Lower lid for wiring
	PST-2530-15A	Steel	IP66	300	400	200	TX-PROM5	N/A	Resistance against impact IK10. Lower lid for wiring
	PST-5070-25A	Steel	IP66	400	400	200	TX-PROM5	N/A	Resistance against impact IK10. Lower lid for wiring
	PST-3040-20A	Steel	IP66	400	400	200	TX-PROM5	N/A	Resistance against impact IK10. Lower lid for wiring
	PST-80100-30A	Steel	IP66	500	600	250	TX-PROM5	N/A	Resistance against impact IK10. Lower lid for wiring
	PST-4060-20A	Steel	IP66	800	700	300	TX-PROM5	N/A	Resistance against impact IK10. Lower lid for wiring